

EN ISO 20345:2022 

DIVENTURE  
**BRENNERO BOA®**  
 70534-03L

**S3S FO \*CI SC LG SR**

**Size:** 36-48  
**Weight:** 740 gr.

**Fit:** 11

**Working Environment:**  
 Building, Wood-metal carpentry,  
 Oil industry, Farming and  
 Gardening



**FEATURES**

**UPPER**  
 Greased Nubuk Dakar Leather  
 Hydro 1,8-2,0 mm

**LINING**  
 3D Green Air 320 gr.

**ANTISLIP LINING**  
 DUALMICRO

**INSOLE**  
 QRS02 Green

**TOE CAP**  
 Fiber cap SXT

**RESISTANCE TO PERFORATION**  
 KX Antiperforation recycled PS

**TYPE**  
 Ankle boot

**SOLE**  
**PU DUAL-DENSITY CCYCLED® SR**  
 Two-component PU sole made from recycled Cycled® material with additional LG and SC requirements and SR characteristics.

**Boa® lace length**  
 M4 - 115cm



**TECHNOLOGIES**

**Removable Insole**  
**QRS02 GREEN**

Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



**Protection elements**

**KX GREEN** RESISTANT TO 3.0 mm. NAILS **fibercap sxt**

Composite toe cap with fiberglass. Resistant to over 200J. Recycled non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



**Lateral stability**  
**dynamicControl technology**





Ergonomic rigid structure. It accommodates the heel, adjusting the foot support and control of the ankle in sideways movements. The plastic material increases protection of the ankle against sharp or pointy objects.



**Torsional stability**  
**STABIL•ACTIVE**


Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



PU - PU SOLE 70		SLIP RESISTANCE	
EN ISO 20345:2022			
<b>BASIC</b> CERAMIC WITH NALS	FORWARD HEEL SLIP $\geq 0.31$	<b>0,39</b>	
	BACKWARD FOREPART SLIP $\geq 0.36$	<b>0,42</b>	
<b>SR</b> CERAMIC WITH GLYCERINE	FORWARD HEEL SLIP $\geq 0.19$	<b>0,20</b>	
	BACKWARD FOREPART SLIP $\geq 0.22$	<b>0,31</b>	

**Electrical features**  


ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

**Other**  
 **FIT TO GO FURTHER™**

A patented closing system with a multi coated stainless steel cable. The BOA® Fit System delivers micro-adjustable precision fit, engineered to perform in the toughest conditions.

